

Eaton® Concrete Pumping EHK007



#	Part No.		Hose I.D.		Hose O.D.		Max Oper Pressure		Burst Pressure		Minimum Bend Radius		Weight		Length		
			DN	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	mtr	ft
EHK007-32-	MXX	100	51	51,0	2.00	70,0	2.76	85	1232	200	2900	275	10.83	3,03	2.04	40-61	100
EHK007-40-	MXX	100	60	63,5	2.50	88,0	3.46	85	1232	200	2900	300	11.81	4,48	3.01	40-61	100
EHK007-48-	MXX	100	80	76,2	3.00	102,0	4.02	85	1232	200	2900	350	13.78	5,46	3.67	40-61	100
EHK007-64-	MXX	100	102	101,6	4.00	130,0	5.12	85	1232	200	2900	400	15.75	8,46	5.69	40-61	100
EHK007-80-	MXX	100	130	127,0	5.00	155,0	6.10	85	1232	200	2900	500	19.69	9,63	6.47	40-61	100
EHK007-96-	MXX	100	150	153,0	6.00	180,0	7.09	85	1232	140	2030	650	25.59	10,99	7.39	40-61	100

Construction:

Tube: Natural and CBR blend

Reinforcement: High tensile steel cords

Cover: Pin-pricked synthetic rubber

Application:

- High pressure concrete pumping

Markets:

- Construction
- Cement placement

Type of Couplings:

- Victaulic male npt

Contact coupling manufacturer for attachment procedure and other coupling recommendations.

Operating Temperature:

-40°C to +70°C
(-40°F to +158°F)